

PLANK SPECIFICATION SHEET

Natural Limed CV - UR - 1002

Product Profile

CollectionChervonWood SpeciesEuropean OakSurface FinishUV Lacquer

Bevel 4 sided Micro- Bevel

Wear Layer Solid European Oak Hardwood

Core Multi-layer plywood

Joining Profile Tongue and Groove

Nested Boards Up to 20%

Wood Grade ABCD, AB(on pre-order only)

Available Sizes: 1900 x 190 x 15/3 mm

2200 x 220 x 20/6 mm


600 x 120 x 15/3 mm (Herringbone)

770 x 125 x 15/3 mm (Chevron)



Natural Limed

Plank Profile



Installation

Installation Method	Floating, Direct Stick
Suitable Substrates	Particle Board, Concrete,
	existing timber - enquire for others
Suitable Applications	Flooring, Walls, Ceilings
Suitable Uses	Residential homes, hospitality,
	retail stores, restaurants, apartments
Underfloor Heating	Hydronic Systems - enquire for others

Technical Specification

15mm Mean CHF Value (kW/m2)	3.7
15mm Mean Smoke Value (%.min)	40
Formaldehyde Emission	E1
Slip Classification	Р3
Moisture Content	8-12%
Smoke Value	64 %/min
Floating	Yes
Direct Stick	Yes

